

page 1/7 ResiCem PRIMER B

Printing date: March 31, 2022

SECTION 1. Identification of the substance or mixture and of the supplier

1.1 Product identifier

Trade Name:

ResiCem "PRIMER B"

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Dental material Uses advised against: No further data

1.3 Details of the supplier of the safety date sheet

Company/Undertaking identification

Manufacturer's Name: SHOFU INC.

Address: 11 Kamitakamatsu-cho, Fukuine, Higashiyama-ku, Kyoto 605-0983, JAPAN

Phone: +81-75-561-1112 Fax: +81-75-275-4795

Section in Charge: Quality Assurance Section

1.4 Emergency Telephone Number

+81-75-561-1112

SECTION 2. Hazards identification

2.1 GHS Classification

PHYSICAL HAZARDS

FLAMMABLE LIQUIDS Category 2

HEALTH HAZARDS

SKIN CORROSION/IRRITATION Category 2
EYE DAMAGE/IRRITATION Category 2A
SENSITIZATION-RESPIRATORY Category 1
SENSITIZATION-SKIN Category 1

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)

Category 3 (narcotic effects)

Other hazards than mentioned above are Not applicable or data available.

2.2 Label elements SYMBOL







GHS02

2 GHS07

GHS08

SIGNAL WORD Danger

HAZARD STATEMENTS

Highly flammable liquid and vapor

Causes skin irritation

May cause an allergic skin reaction

Causes serious eye irritation

May cause allergy or asthma symptoms or breathing difficulties if inhaled

Version Number 5



page 2/7 ResiCem PRIMER B

Printing date: March 31, 2022

May cause drowsiness or dizziness

PRECAUTIONARY STATEMENTS

[Prevention]

Do not handle until all safety precautions have been read and understood.

Wear protective gloves and eye/face protection.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Keep away from ignition sources such as heat/sparks/open flames-No smoking.

Keep container tightly closed.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

[Response]

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

If skin irritation or rash occurs: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Call a POISON CENTER/doctor if you feel unwell.

[Storage]

Store container tightly closed in cool/well-ventilated place (Keep refrigerated when not in use).

[Disposal]

Dispose of contents and container in accordance with regulation.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

SECTION 3. Composition/information on ingredients

3.1 Chemical characterization: Mixtures

3.2 Ingredients and composition:

Component	CAS-No	Weight %
2-Hydroxy Ethyl Methacrylate	868-77-9	40-50
Acetone	67-64-1	10-30
Acrylic adhesive monomer	_	
Others	_	

3.3 Additional information: For the wording of the listed risk phrases refer to section 2

Version Number 5



page 3/7 ResiCem PRIMER B

Printing date: March 31, 2022

SECTION 4. First-aid measures

4.1 Description of first aid measures

Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if

present. and easy to do. If eye irritation persists, get medical advice/attention.

Skin contact: Wash immediately with soap and plenty of water. If on skin, skin irritation, get

medical advice/attention.

Ingestion: Rinse mouth and seek medical advice if necessary.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

If symptom concerning breath goes out, call a POISON CENTER or doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5. Fire-fighting measures

5.1 Extinguishing Media:

Foam, CO₂, Powder, Dry sand

5.2 Special hazards arising from the substance or mixture:

If not dangerous, the container is move from the fire district.

Fire fighting operation should be done from upwind position, with wearing protective equipment.

5.3 Advice for firefighters:

Wear fire protective cloth and self-contained breathing apparatus, if necessary.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid contact with eyes and skin. Wear appropriate protective equipment.

6.2 Environmental Precautions:

Do not allow product to reach sewage system or water bodies.

Do not allow to enter the ground/soil.

6.3 Methods and material for containment and cleaning Up:

Wipe up and discard in a stable container.

6.4 Reference to other section:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7. Handling and storage

7.1 Precautions for safe handling:

Use appropriate protective equipment such as safety glasses to avoid skin, eye contact, inhalation of vapors, etc.

Handle in a well ventilated place. Handle with fire prohibited.

Avoid contact with hot items, sparks, fire, strong oxidants.



page 4/7 ResiCem PRIMER B

Printing date: March 31, 2022

7.2 Conditions for safe storage, including any incompatibilities:

Store in a cool and dark area with container tightly closed.

Separated from strong oxidants (Keep refrigerated when not in use).

7.3 Specific end use(s):

No further relevant information available.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters:

Exposure limits:

	ACGIH	NIOSH	OSHA-Final PELs
Acetone	500 ppm TWA	250 ppm TWA	1000 ppm TWA
	750 ppm STEL	(590 mg/m ³ TWA)	2400 mg/m ³ TWA
		2500 ppm IDLH	

8.2 Exposure controls:

Respiratory Protection:

Not required (use protective gas mask for organic gas, if necessary)

Skin Protection:

Hand Protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

Eye Protection: Safety goggles

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Appearance/Odor/Colour: Colorless liquid with sweet odor.

Odour threshold Not determined.

Version Number 5



page 5/7 ResiCem PRIMER B

Printing date: March 31, 2022

Not determined. Hq Melting point/freezing point Not determined. **Boiling Point:** Not determined. Flash point: -12 °C (closed) Evaporation rate Not determined. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits Not determined. Vapour pressure Not determined. Vapour density Not determined. Relative Density: 1.1 (water=1) Solubility: water solubility Soluble

Partition coefficient: n-octanol/water
Auto-ignition temperature
Decomposition temperature
Viscosity
Not determined.
Not determined.
Not determined.
Not determined.
Not applicable.
Oxidising properties
Not applicable.

9.2 Other information:

No further relevant information available.

SECTION 10. Stability and reactivity

10.1 Reactivity:

No further relevant information available.

10.2 Chemical stability:

Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions:

No dangerous reactions known.

10.4 Condition to Avoid:

Excessive heat (high temperature), open flames, ignition source, and exposure to sunlight.

10.5 Incompatible materials:

Strong oxidizing materials.

10.6 Hazardous Decomposition Products:

None under normal conditions of storage and use.

SECTION 11. Toxicological information

11.1 Information on toxicological effects:

Acute toxicity: 2-Hydroxy Ethyl Methacrylate;

Oral rat LD50 > 4000 mg/kgDermal rabbit LD50 > 3000 mg/kgAcetone: Oral rat LD50 5800 mg/kg > 7400 mg/kg Dermal LD50 rabbit

Inhalation rat LC50 32000 ppm/4H

Skin corrosion/irritation: Skin Irrit. 2; H315 Causes skin irritation.

Eye damage/irritation: Eye Irrit. 2A; H319 Causes serious eye irritation.

Version Number 5



page 6/7 ResiCem PRIMER B

Printing date: March 31, 2022

Sensitization to the respiratory tract:

Resp. Sens. 1; H334 May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitization: Skin Sens. 1; H317 May cause an allergic skin reaction.

Germ cell mutagenicity/Genotoxicity:

Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure):

STOT SE 3; H336 May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure):

Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards:

No further relevant information available.

SECTION 12. Ecological information

12.1 Toxicity:

Acetone:

Fish toxicity: Fathead minnow; LC50/96H >100mg/L

12.2 Persistence and degradability:

No further relevant information available.

12.3 Bioaccumulative potential:

No further relevant information available.

12.4 Mobility in soil:

No further relevant information available.

12.5 Results of PBT and vPvB assessment:

Not applicable.

12.6 Other adverse effects:

No further relevant information available.

SECTION 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of contents/container to in accordance with local/regional/national/international regulations.

SECTION 14. Transport information

14.1 UN number: 1090

14.2 UN proper shipping name: Acetone, solution14.3 Transport hazard class(es): 3 Flammable liquids.

14.4 Packing group:

14.5 Environmental hazards: No further relevant information available.

14.6 Special precautions for user: Not applicable.

Version Number 5



page 7/7 ResiCem PRIMER B

Printing date: March 31, 2022

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable.

SECTION 15. Regulatory informati

Follow all regulations in your country.

SECTION 16. Other information

This product is intended for use by dental professionals (instrument/material).

NFPA ratings for USA (scale 0-4)

2-Hydroxy Ethyl Methacrylate;





Heaith = 1 Fire = 1 Reactivity = 1



Heaith = 1 Fire = 3 Reactivity = 0

HMIS-Ratings (Scale 0-4)

2-Hydroxy Ethyl Methacrylate;

Health Hazard	1
Fire Hazard	1
Reactivity	1

Heaith = 1 Fire = 1 Reactivity = 1

Acetone;

Health Hazard	1
Fire Hazard	3
Reactivity	0

Heaith = 1 Fire = 3 Reactivity = 0

Relevant phrases:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Abbreviations and acronyms:

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative